

HMK® R99 Stripper-Thinner

Strips sealer, heavy wax coatings and impregnators.

Can be used as a thinner for HMK® Sealers and Impregnators.

For internal and external use.



HMK® R99 is a special ready to use stripper/thinner for cleaning and removing wax coatings, sealants and impregnators. Small areas can be treated and renovated quickly and easily. R99 also removes oil and fat from natural and artificial stone and can be used on tools and equipment. Polished surfaces will not be damaged by R99.

For removing sealants and impregnators on larger areas we recommend the use of HMK® R80 Stripper Stain Remover.

Important: Do not apply in direct sunlight. Do not apply on rubber, plastic, perspex, lacquered surfaces, polished wood and solvent intolerant materials. Remove all foodstuffs from the area before work is commenced.

Instructions: Protect adjacent surfaces and ensure adequate ventilation. If under floor heating exists, switch it off and allow the surface to cool. Working on a small area at a time, apply a generous coat of R99 undiluted onto the surface using a stiff brush, scrubbing brush or suitable pad and work into the surface. Leave it for a short time, but do not allow to dry, and scrub the area again vigorously. Immediately remove the residue with a colourless cloth or paper towel and wipe the surface dry. If patches remain untreated after drying, repeat the treatment as necessary. After treatment scrub the treated area using HMK® R55 Intensive Cleaner -acid free- diluted approx 1:10 with clean water and remove the residue. Rinse the surface thoroughly with clean water to complete the procedure.

When using a wet vacuum we recommend that you add HMK® Z102 Defoamer to the water to regulate the amount of foam.

Coverage: About 3-5m²/litre.

Warning: Chemical product. Contains naphtha, petroleum product. Flammable. Keep away from heat and flame. Harmful or fatal if swallowed or inhaled. Avoid eye/skin contact and breathing vapour or mist. If exposed, wash/flush with water and seek medical attention immediately. Keep out of the reach of children. Use with adequate ventilation. See Material Safety Data Sheet for more detailed information.

Packaging: 12 x 1 litre bottles/box; 4 x 5 litre cans/box.

Storage: Store in cool place. Keep lid tightly closed.

Testing: Always test the product in an inconspicuous area to evaluate suitability, coverage and performance. Do not use the product in temperatures below 12 and above 25 °C.

Limitation of liability: The liability of HMK® Moeller Stonecare for defective products and any claims for damages whatsoever is limited to the purchase price of the products. HMK® Moeller Stonecare shall not be liable for any consequential damages. No other warranty or representation is made or implied.